



- Lierspecificaties**
- Type : Elektrische ankerlier ECA-.....-KB
 - Werklast (SWL) : 1500 tot 4000 kg op laag 1
 - Houkracht : 8000 tot 11500 kg op laag 1
 - Inhaalsnelheid : ca. 10 m/min op laag 1
 - Trommel : $\varnothing 180 \times 280$ mm
 - Kabelberging : 72 meter $\varnothing 26$ mm op 7 lagen incl. 3 veiligheidswindingen
 - Motorvermogen :
 - Voeding : 400V 50Hz 3ph
 - Beschermklasse :
 - Rem : Fail-safe rem
 - Conservering :
 - Inclusief opties : Vrijloopp koppeling
 - Gebruiksklasse : Bandrem handbediend
 - Gebruikstemperatuur : -10° tot +40° Celsius
 - Kabel aflooprichting : Links boven
- LET OP** : Verseizingsafstand min. 4 meter vanaf hartlijn trommel tot hartlijn 1e schijf, uitgaande van links/rechts geslagen kabel, indien geen andere compenserende maatregelen genomen zijn.

POS.No	Qty.	ARTICLE or DESIGNATION	MATERIAL or DRAWING NO.	DIMENSIONS	
		DROMECC bv	SCALE: 1:6	COMMENTS: Scherpe kanten breken	
		Steenoven 13	UNIT: mm		
		3911 TX RHENEN	DATE: 29.03.2018		
		The Netherlands	DRAWN BY: JWVR		
DESIGNATION				DRAWING - REV.No	SIZE
DL-A-3-A				DL-A-3-E	A2
Toleranties according to ISO 2768-ML, unless otherwise specified complete welding a = 0,5 x thinnest sheet +1 Copyright Dromec bv - Notices to third parties is only allowed with written permission					