



Winchtype : Electric anchor winch EWA-350-KB  
 Serienummer : W21368  
 Weight : App. 125kg  
 Working load : 350kg  
 Holding load : 2400kg  
 Mounting position : Motor and mounting surface horizontal  
 Hauling speed : App. 13m/min  
 Chain wheel : 14mm studlink max. angle 55°  
 Motor power : 1.3kW S2-10min  
 Power supply : 400V  
 Protection class : IP56 TENV  
 Brake : Fail safe brake 150% of SWL  
 Coating : 3-layer coating RAL5010  
 Including options : Hand operated band brake  
                           : Hand operated freewheel clutch  
 User class : T5-L2-M5 (vlg FEM 1.001 en ISO 4301/1)  
 User temp. : -10° till +40° Celsius

STATUS:	TITLE: EWA-350-KB	DRAWING - REV.No:	W21368	
Released	<b>DROME C</b> drives & winches	DRAWN BY: PM	SHEET: 1	D
	www.dromec.nl	CHECKED BY:	Am. PR:	C
	+31(0)317-681155	UNIT OF MEASURE: mm		B
		FORMAT: A2		A
		SCALE: 1:4		REV TEXT
	DATE: 01.12.2021	COMMENT: Scherpe kanten breken		DATE NM
Tolerances according to ISO 2768-mL, unless stated otherwise around welding a = 1/2 x thinnest sheet thickness +1. Copyright Dromec bv - Notifications to third parties are only permitted with written permission.				